



Moneysworth & Best
120 Midair Court
Brampton, ON, L6T 5V1
Canada
905-790-0650

PRODUCT: 29631_Dark Green BCS 127g/4.5oz

CODE: 29631

SECTION 01: IDENTIFICATION

Product Identity..... 29631_Dark Green BCS 127g/4.5oz
Product Item Numbers..... 29631
Supplier..... Moneysworth & Best
120 Midair Court
Brampton, ON
Canada
L6T-5V1
905-790-0650
24 hour emergency telephone number.... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 424-9300.
Recommended Use..... Leather Coloring.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification:
Physical Hazards..... Gases Under Pressure - Liquefied Gas. Flammable Aerosols - Category 2.
Health Hazards..... Eye Damage/Irritation - Category 2A. Crinogenicity Category 1A. Germ Cell Mutagenicity - Category 1B. Reproductive Toxicity - Category 2. Specific Target Organ Toxicity, Repeated Exposure - Category 1. Specific Target Organ Toxicity, Single Exposure Category 3 narcotic effects .
Environmental Hazards..... Hazardous to the aquatic environment, long-term hazard Category 2 . Hazardous to the aquatic environment, acute hazard Category 2 .

Label Elements:
Signal Word..... DANGER.
Hazard Statement..... H223:Flammable aerosol. H372:Causes damage to organs through prolonged or repeated exposure. H335:May cause respiratory irritation. H350:May cause cancer. H340:May cause genetic defects. H280:Contains gas under pressure; may explode if heated (L). H229:Pressurized container: may burst if heated (1). H319:Causes serious eye irritation. H336:May cause drowsiness or dizziness. H361:Suspected of damaging fertility or the unborn child. Toxic to aquatic life with long lasting effects.

Precautionary Statements:
Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251:Do not pierce or burn, even after use. P260:Do not breathe dust/ fume/ gas/ mist/ vapours /spray. P270:Do not eat, drink, or smoke when using this product. P211:Do not spray on an open flame or other ignition source. P271:Use only outdoors or in a well-ventilated area. P203: Obtain, read and follow all safety instructions before use. P280:Wear protective gloves/ protective clothing/ eye protection/ face protection. P264:Wash hand thoroughly after handling. P318: If exposed or concerned, get medical advice.
Response..... P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P319:Get medical help if you feel unwell. P337+P317:If eye irritation persists: Get medical help.
Storage..... P403:Store in a well ventilated place . P233:Keep container tightly closed. P405: Store locked up. P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.
Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|----------------------------|----------|-------|
| Acetone | 67-64-1 | 15-40 |
| n-Butane | 106-97-8 | 10-30 |
| Ethyl Acetate | 141-78-6 | 7-13 |

PRODUCT: 29631_Dark Green BCS 127g/4.5oz

CODE: 29631

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| | | |
|---------------------------------------|-----------|-------|
| Xylene | 1330-20-7 | 5-10 |
| Propylene Glycol Methyl Ether Acetate | 108-65-6 | 1-5 |
| Ethyl Benzene | 1000-41-4 | 1-5 |
| Methyl Ethyl Ketone | 78-93-3 | 1-5 |
| Carbon black | 1333-86-4 | 0.1-1 |
| COPPER | 7440-50-8 | 0-1 |
| Other Ingredient(s) | | 10-30 |

SECTION 04: FIRST-AID MEASURES

| | |
|--|--|
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. |
| Eye Contact..... | Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Get medical attention if irritation persists. |
| Skin Contact..... | Remove contaminated clothing. Launder clothing before reuse. Wash thoroughly with soap and lukewarm water. If irritation occurs consult with your doctor. |
| Ingestion..... | Not likely to be ingested. If occurs, do not give anything by mouth to an unconscious person. Do not induce vomiting, get medical attention. Obtain medical advice. |
| Most important symptoms/effects, acute .. and delayed | Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|--|
| Suitable Extinguishing Media..... | Dry chemical powder. Carbon dioxide. Foam, water spray or fog. |
| Unsuitable Extinguishing Media..... | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific Hazards Arising from the Chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. |
| Special Protective Equipment and .. Precautions for Firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do. |
| General Fire Hazards..... | Extremely flammable aerosol. |

SECTION 06: ACCIDENTAL RELEASE MEASURES

| | |
|--|--|
| Personal Precautions, Protective .. Equipment and Emergency Procedures | Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08). |
| Methods and Materials for Containment .. and Cleaning Up | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| Environmental Precautions..... | Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination. |

SECTION 07: HANDLING AND STORAGE

| | |
|---|---|
| Precautions for Safe Handling..... | Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling . Wear appropriate protective equipment. |
| Conditions for Safe Storage including any Incompatibilities | Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10). |

PRODUCT: 29631_Dark Green BCS 127g/4.5oz

CODE: 29631

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|---------------------------------------|-----------------------|-------------------|--------------------------------------|----------------------------------|----------------------------------|
| Acetone | 250 ppm | 500 ppm | 1,000 ppm (2,400 mg/m ³) | Not available | Not available |
| n-Butane | 800 ppm | Not available | Not available | Not available | Not available |
| Ethyl Acetate | 400 ppm | Not available | 400 ppm (1,400 mg/m ³) | Not available | Not available |
| Xylene | 50 ppm | 150 ppm | 100 ppm (435 mg/m ³) | Not established | Not established |
| Propylene Glycol Methyl Ether Acetate | Not established | Not established | Not established | Not established | Not established |
| Ethyl Benzene | 100 ppm | 125 ppm | 100 ppm | No data | 100 ppm |
| Methyl Ethyl Ketone | 200 ppm | 300 ppm | 200 ppm (590 mg/m ³) | 300 ppm (885 mg/m ³) | 200 ppm (590 mg/m ³) |
| Carbon black | 3.5 mg/m ³ | Not established | 3.5 mg/m ³ | Not established | 3.5 mg/m ³ |
| COPPER | 0.2 mg/m ³ | | | | |

Appropriate Engineering Controls..... Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ground all equipment and cylinders before use.

Individual Protection Measures:

Eye/Face Protection..... Prevent eye contact, wear safety glasses in the event that eye contact is possible.

Skin Protection..... Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.

Respiratory Protection..... Use approved NIOSH respirators for emergencies.

Thermal Hazards..... When necessary, wear appropriate thermal protective clothing.

General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Physical State..... | Liquid. |
| Physical Appearance..... | Aerosol. |
| Odour..... | Not available. |
| Odour Threshold (ppm)..... | Not available. |
| pH..... | Not available. |
| Melting Point (°C)..... | -187.6 °C (-305.68 °F). |
| Boiling Point (°C)..... | -42.1°C (-43.78°F). |
| Flash Point (°C), Method..... | -104.4 °C (-156.0 °F). |
| Evaporation Rate (n-Butyl Acetate = 1)..... | Not available. |
| Flammability (solid, gas)..... | Not applicable. |
| Lower Explosive Limit (% vol)..... | 1.9% estimated. |
| Upper Explosive Limit (% vol)..... | 12.8% estimated. |
| Vapour Pressure (psig)..... | 2248.82 hPa estimated. |
| Vapour Density (Air=1)..... | Not available. |
| Relative Density..... | not available. |
| Solubility in water..... | Not available . |
| Partition Coefficient (n-Octanol/Water)..... | Not available. |
| VOC Content..... | 3.44 lbs/gal Material 411.93 g/l Material 5.16 lbs/gal Regulatory 617.86 g/l Regulatory. |
| Auto Ignition Temperature (Propellant), °C | 287.78 °C (550 °F) estimated. |
| Density (20 °C)..... | 6.15 lbs/gal. |
| Specific Gravity | 0.74. |
| Percent Volatile..... | 91.57. |
| Heat of Combustion..... | 26.88 kJ/g estimated. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | Product not reactive under normal conditions of use. |
| Chemical Stability..... | Stable at normal temperatures and pressures. |
| Possibility of Hazardous Reactions..... | Will not occur. |
| Conditions to Avoid..... | Avoid sources of heat and flame, and electrostatic charge. |
| Incompatible Materials..... | Avoid contacting with oxidizers. |
| Hazardous Decomposition Products..... | No hazardous decomposition products when stored and handled correctly. |

PRODUCT: 29631_Dark Green BCS 127g/4.5oz

CODE: 29631

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|---------------------------------------|-----------------------------|---|
| Acetone | 71 mg/L (Rat - 4 hrs) | 5,800 mg/kg (Oral - Rat); >15,800 mg/kg (Dermal - Rabbit) |
| n-Butane | 658 mg/L (Rat - 4 hrs) | Not available |
| Ethyl Acetate | 28.8-57.7 mg/L (Rat - 4hrs) | 10,200 mg/kg (Oral - Rat); >18,000 mg/kg (Dermal - Rabbit) |
| Xylene | 27.6 mg/L (Rat - 4 hrs) | 3,253 mg/kg (Oral - Rat); 12,180 mg/kg (Dermal - Rabbit) |
| Propylene Glycol Methyl Ether Acetate | 3,350mg/m3 (8hrs) | 8,532mg/kg (Oral - Rat); 5,000mg/kg (Dermal - Rabbit) |
| Ethyl Benzene | No data | 3,500 mg/Kg (oral-rat) |
| Methyl Ethyl Ketone | >5,000 ppm (Rat - 6hrs) | 3,400 mg/kg (Oral - Rat); >8,000 mg/kg (Dermal - Rabbit) |
| Carbon black | Not available | >10,000 mg/kg (Oral - Rat); 3,000 mg/kg (Dermal - Rabbit) |
| COPPER | NOT AVAILABLE | ORL-DOM LDLo: 18,000-18,200mg/kg |

Information on Likely Routes of Exposure:

| | |
|--|--|
| Routes of entry - Inhalation..... | Yes. May cause irritation of respiratory tract. |
| Routes of entry - Skin & Eye..... | Yes. Direct contact with eyes may cause temporary irritation. May cause irritation. |
| Routes of entry - Ingestion..... | Harmful if swallowed. |
| Routes of entry - Skin Absorption..... | No. |
| Symptoms Related to the Physical, | Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. |
| Chemical and Toxicological Characteristics | Harmful if swallowed. Narcotic effects . |
| Acute Toxicity..... | Causes skin irritation. |
| Skin Corrosion/Irritation..... | Causes serious eye irritation. |
| Serious Eye Damage/Eye Irritation..... | Not known to be a sensitizer. |
| Respiratory or Skin Sensitization..... | May cause genetic defects. |
| Germ Cell Mutagenicity..... | Suspected to have carcinogenic effect . |
| Carcinogenicity..... | Suspected to have reproductive effect . |
| Reproductive Toxicity..... | Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness. |
| STOT - Single Exposure..... | May cause damage to the organs through prolonged or repeated exposure. |
| STOT - Repeated Exposure..... | No data available . |
| Aspiration Hazard..... | Prolonged inhalation may be harmful. |
| Chronic Effects..... | |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|-------------------------------------|---|
| Ecotoxicity..... | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. |
| Persistence and degradability | The product itself has not been tested. |
| Bioaccumulation Potential..... | The product itself has not been tested. |
| Mobility in Soil..... | The product itself has not been tested. |
| Other Adverse Effects..... | None Known. |

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

| | |
|--------------------------------|--|
| TDG (Canada- Road)..... | UN number UN1950 UN proper shipping name Aerosols, Flammable Class 2.1 Transport hazard class(es) Subsidiary risk - Packing group Not applicable. Environmental hazards Not available. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. . |
| IATA (International- Air)..... | UN number UN1950 UN proper shipping name Aerosols, Flammable Class 2.1 Transport hazard class(es) Subsidiary risk - Label(s) 2.1 Packing group Not applicable. Environmental hazards No. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Passenger and cargo Allowed. aircraft Other information Cargo aircraft only Allowed. . |

PRODUCT: 29631_Dark Green BCS 127g/4.5oz

CODE: 29631

SECTION 14: TRANSPORT INFORMATION

IMDG (International- Marine)..... UN number UN1950 UN proper shipping name Aerosols, Flammable, MARINE POLLUTANT Class 2.1 Transport hazard class(es) Subsidiary risk - Label(s) 2.1 Packing group Not applicable. Marine pollutant Yes Environmental hazards EmS Not available. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code .

SECTION 15: REGULATORY INFORMATION

Canada Regulations:..... Precursor Control Regulations ACETONE (CAS 67-64-1) Class B METHYL ETHYL KETONE (CAS 78-93-3) Class B. Controlled Drugs and Substances Act: Not regulated. Export Control List (CEPA 1999, Schedule 3): Not listed. Greenhouse Gases: Not listed.

TSCA Inventory Status..... All components are either listed or exempt from the TSCA.

California Proposition 65..... This product contains a chemical known to the State of California to cause cancer. ETHYLBENZENE (CAS 100-41-4), TITANIUM DIOXIDE (CAS 13463-67-7).

SECTION 16: OTHER INFORMATION

Disclaimer..... This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS. The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by Regulatory Affairs
Latest Revision 2022-02-20